# LINDBERG GEOLOGIC CONSULTING

Post Office Box 306 Cutten California 95534 (707) 442-6000

December 22, 2022

Ms. Marion Collamer Lost Creek Farms, LLC 600 F Street, Ste #3, Box 208 Arcata, California 95521 Project No: 0496.00

MAR 2 3 2023
Humboldt County
PLANKING

Subject:

Hydrologic Isolation from Surface Waters, Well WCR2009-007349 (e0096711)

Perimeter (Rim) Road, Honeydew, APN: 211-184-006 Apps 10820

# To Whom It May Concern:

As requested, Lindberg Geologic Consulting has assessed an existing permitted well on the above-referenced parcel to estimate its potential for hydrologic connectivity with any nearby surface waters, other wells, or wetlands, and if pumping well WCR2009-007349 might significantly affect nearby surface waters. The nearest watercourses in the vicinity of this well are Westlund Creek, a perennial stream, and an ephemeral tributary of perennial stream of Bull Creek (Figure 1).

A California-Certified Engineering Geologist visited this well site on December 9, 2022, to observe the subject well and local site conditions. Based on our observations, research, and our professional experience, it is our opinion the subject well has a low likelihood of being hydrologically connected to nearby surface waters in any manner that could significantly affect adjacent surface waters, springs, wetlands, or other wells in the vicinity. We define the "vicinity" as the area within a 1,000-foot radius of the subject well (Figure 1), an area that encompasses approximately 72 acres. The proposed use of this well is to irrigate cannabis. We are not aware of the volume of water to be extracted or what the pumping schedule might be but expect that that information is provided elsewhere in the application.

Based on Humboldt County's WebGIS and the Assessor's Parcel Map (Figure 2), parcel 211-184-006 (Figure 2) encompasses approximately 41 acres. Our GPS located the subject well at latitude 40.25344° north, and longitude 124.00011° west (±9'). This well is in Section 31, T2S, R2E, and is 200 feet deep. The wellhead is at an elevation of approximately 2,100 feet (Figure 1) and the elevation of the bottom of the well is therefore 1,900 feet.

The Humboldt County WebGIS shows three watercourses within one mile of the well site. To the north more than 1,450 feet is an ephemeral tributary of Bull Creek. More than 1,200 feet to the southwest is perennial Westlund Creek. To the west more than 1,700 feet is a perennial tributary of Westlund Creek. Based on interpolation from the Weott topographic quadrangle map (1969), (Figure 1), and the Humboldt County WebGIS, the elevation of the subject well is 2,100 feet. The elevation of Westlund Creek, the nearest watercourse, is 1,620 feet. The bottom elevation of well WCR2009-007349 is 1,900 feet, making Westlund Creek 280 feet lower than the total depth of the well.

December 22, 2022

Marion Collamer, Well-007349, Project No: 0496.00

Page 2

The location of well WCR2009-007349 is shown approximately on the attached figures, and was drilled by Fisch Drilling, of Hydesville, in June 2009, under Humboldt County well permit #08/09-0639. Fisch Drilling is a licensed well-drilling contractor (C-57 #683865). Fisch Drilling submitted their attached well completion report (DWR 188) on June 27, 2009. The driller estimated a yield of 20 gpm on June 18, 2009, based on a 4-hour air lift pump test. Total drawdown during the pump test was reported as 200 feet (sic).

Total depth of this well is 200 feet. The borehole diameter is 10-inches from the surface to 200-feet. From the surface to 100 feet, a 5-inch diameter blank (unslotted) PVC casing was installed. From 100- to 200-feet, 5-inch diameter, PVC well screen with 0.032 milled slots was installed. Per County requirements, a bentonite surface sanitary seal was installed from the surface to 20 feet. Below the bentonite seal, the driller reported filling the annulus with 3/8-inch pea gravel. The well is cased and sealed through any potential shallow subsurface aquifers in the uppermost 20 feet as required by county regulation. Depth to first water was reported at 110-feet, and depth to static water in the completed developed well was reported to be 100 feet bgs when the driller conducted the pump test on June 18, 2009.

There is only one spring mapped on the USGS topographic maps within one mile of the subject well. That spring is more than 3,200 feet to the west, in Section 36, at an elevation of 1,920 feet. The next closest spring is more than one mile (>5,780 feet) to the northwest in Section 25, at an elevation of approximately 2,360 feet. The next closest springs appear to be more than 2 miles west, on the Mann Ranch in Section 35. Based on the USGS topographic maps, there are no other springs mapped within one mile of the subject well.

This parcel is located within California's Coast Range Geomorphic Province, in the Central Belt of the Franciscan Complex (McLaughlin et at., 2000), a seismically active region in which large earthquakes are expected to occur during the economic life span (70 years) of any developments on the subject property. Geologic mapping by McLaughlin shows that the site is underlain by the Yager Terrane (y1) of the Coastal Belt of the Franciscan Complex, as shown in Figure 4.

According to the NRCS Web Soil Survey, the near-surface soils consist of loam to a depth of 21-inches, gravelly loam to 46-inches, and very gravelly fine sandy loam to 79-inches. Soils are interpreted to be uniformly distributed across that portion of the subject parcel underlain by the Yager Terrane of the Coastal Belt of the Franciscan Complex.

Materials described on the geologic log of the driller's well completion report (attached) include "Fractured Weathered Bedrock" from the ground surface to 68 feet. From 68-feet to 200-feet the driller logged "Fractured Bedrock". First water was encountered at 110 feet and stabilized at 100 feet. At the location of the subject well, the elevation of the first water-bearing aquifer unit is thus at an elevation of approximately 2,000 feet, based on our interpretation of the driller's report.

December 22, 2022

Marion Collamer, Well-007349, Project No: 0496.00

Page 3

Earth materials encountered in the borehole are likely Yager Terrane sandstone and argillite of the Coastal Belt Franciscan Complex, as mapped by McLaughlin et al., (2000). Sheared, fractured, and folded metasedimentary rock materials can have variable hydraulic conductivity, but can also constitute significant aquifers. We interpret the "Fractured Bedrock" as described by the driller, to be sandstone of the Coastal Belt of the Franciscan Complex. That section of the profile apparently has favorable hydraulic conductivity, making it in our interpretation, the primary water bearing lithographic unit in the subject well.

A geologic cross section of the area after McLaughlin et al., (2000) shows the structural and stratigraphic relationships between the regional geologic units (Figure 5). The Coastal Belt Yager Terrane is shown dipping east and bounded by thrust fault plane contacts. On-site, no attitude of the rock units could be observed because they are mantled with soil and colluvium and obscured by vegetation. We interpret the faults in the subsurface to be significant hydrogeologic boundaries of low permeability (due to grinding and shearing along the fault planes), effectively separating units of the Coastal Belt Franciscan Complex from each other hydrologically, and thereby limiting groundwater flow between the fault-bound units.

Based on observations, review of pertinent and available information, and our experience, it is our professional opinion that this well has a low potential of having any direct or significant connection to proximal surface waters. First water was reportedly encountered at 110 feet and stabilized to a static water level at 100 feet bgs. This well is sealed with bentonite through the upper 20 feet of any potential unconfined, near-surface aquifers with which it might communicate hydraulically through the borehole.

When considered with the stratigraphy, and the underlying geologic structure, plus the distances (horizontal and vertically) from the nearest surface waters, and the depth of the producing zone of this well (100 to 200 feet), as well as the position of the well relative to the nearest surface waters in the vicinity, we conclude that the depth of the surface seal, is sufficient to preclude the potential for hydraulic connectivity with perennial surface waters, of which there are none closer than 1,000 feet in perennial Westlund Creek at an elevation of 1,620 feet. Thus, the water source from which this well draws appears to be a subsurface aquifer not demonstrably or significantly connected to any surface waters or unconfined, near-surface aquifer(s). This well appears, in our professional opinion, likely to be hydraulically isolated from nearby surface waters, springs, wells, or wetlands.

According to the driller, the estimated yield of this well was 20 gallons per minute (gpm) on June 18, 2009. A nonsensical drawdown of 200-feet was reported after Fisch Drilling's four-hour airlift pump test. Regardless, at 20 gpm, this well would potentially produce 28,800 gallons per day. As noted in the well completion report, this capacity may not be representative of this well's long-term yield. Additional drawdown and recovery testing would be necessary to estimate a sustainable long-term yield of the site well.

December 22, 2022

Marion Collamer, Well-007349, Project No: 0496.00

Page 4

This subject well does not appear to be hydrologically connected to, or capable of influencing surface water flows in the nearest watercourse, perennial Westlund Creek. Nor does this well appear likely to be hydrologically connected to any local springs or ephemeral wetlands. Given the distances involved, and the elevation differences between the subject well, and the nearest surface waters and springs, the potential for significant hydrologic connectivity between surface water and groundwater in the Yager Terrane Coastal Belt Franciscan aquifer(s) appears unlikely.

As discussed, on the USGS topographic quadrangle maps, there are no springs mapped within 1,000 feet of the subject well. There are no significant (mapped) springs or wetlands within one half mile of this subject well.

We have researched the California Department of Water Resources' database to find permitted wells within 1,000 feet of the subject well. Based on the information available at the present time, there are no wells that meet that criterion. The closest well, WCR2018-009210, is on parcel 211-183-008, more than 1,000 feet to the northeast. Well WCR2018-009210 is in Section 30, it is 240 deep, at an elevation of 2,240 feet. Well WCR2018-009210 is on a separate parcel, but one that is under the same ownership and control as the subject well.

As groundwater mimics topography and moves in response to the force of gravity, in general any near surface unconfined aquifer will flow down slope in a direction subparallel to topography. The ground surface slopes primarily to the southwest; thus, the near surface unconfined aquifer flows toward Westlund Creek. At the time of our site visit, there was installed a pump in the subject well.

In our professional opinion, it appears that the aquifer tapped by the subject well is recharged by water infiltrating through the soil, and the argillite and sandstone bedrock from upslope source areas both proximal and distal to the well site. Ephemeral watercourses and flow channels in the vicinity also contribute recharge when they flow during runoff generating storm events.

The United States Department of Agriculture's (USDA), Natural Resources Conservation Service's (NRCS), online Web Soil Survey, shows the subject well within soils of the Wirefence-Windynip-Devilshole complex, on slopes of 5 to 30 percent, (#646, Figure 7), which the NRCS describes as a well-drained soil. The Web Soil Survey's unit description is attached to this report. Mean annual precipitation is listed by the NRCS as 60 to 100 inches per year. Capacity of the most limiting soil layer to transmit water (Ksat) is described as moderately high to high (0.60 to 2.00 in/hr) with a depth to the water table of greater than 80 inches.

If during the wet season, only ten percent of the "low end" precipitation estimation of 60 inches is absorbed by the soils/bedrock and does not flow across the ground surface and into local watercourses (or be lost to evapotranspiration), then approximately 20.5 acre-feet, or more than 6.6 million gallons of water per year (MGPY), may be expected to recharge the local aquifer below this 41-acre subject property. Given the same amount of precipitation (60") and the same 10 percent partitioned to recharge, then within the 1,000-foot radius vicinity of the subject well,

December 22, 2022

Marion Collamer, Well-007349, Project No: 0496.00

Page 5

recharge can be estimated. Recharge within the 72 acres enclosed by a circle having a 1,000-foot radius, would be 36 acre-feet, and more than 11 MGPY. Our estimates are conservative; United States Geological Survey (USGS) researchers estimate that in northwest California, approximately 33 percent of precipitation goes to recharge (Flint, et al., 2103).

On March 28, 2022, Governor Newsom issued an executive order (N-7-22) relating to the ongoing drought in California. In executive order N-7-22, the governor outlined measures the state will undertake to avoid and ameliorate the negative impacts of the current drought. Among these measures, it was ordered that counties, cities, and other public agencies have been prohibited from approving permits for new groundwater wells (or alteration of existing wells) in basins "subject to the Sustainable Groundwater Management Act and classified as medium- or high-priority without first obtaining written verification from a Groundwater Sustainability Agency managing the basin or area of the basin where the well is proposed". This well on Perimeter (Rim) Road, is not within a basin subject to the Act, and there has been no Groundwater Sustainability Agency established with authority over the area where this permitted well is sited.

The Governor's order also states that counties, cities, and other public agencies are prohibited from issuing permits for new groundwater wells (or altering existing wells) "without first determining that extraction of groundwater from the proposed well is (1) not likely to interfere with the production and functioning of existing nearby wells, and (2) not likely to cause subsidence that would adversely impact or damage nearby infrastructure". The conditions in the Order are not applicable to "wells that provide less than two acre-feet per year of groundwater for individual domestic users, or that will exclusively provide groundwater to public water supply systems."

Based on our observations, research, and experience, it is our professional opinion that the well WCR2009-007349, located Perimeter (Rim) Road, Honeydew, on APN 211-184-006, has a low likelihood of being hydrologically connected to nearby surface waters, springs, or wells in any manner that might have a significant negative impact or effect on such proximal surface waters, springs, or wells.

Please contact us if you have questions or concerns regarding our findings and conclusions.

Sincerely,

David N. Lindberg, CEG

David N. L'mdl

Lindberg Geologic Consulting

DNL:sll

December 22, 2022

Marion Collamer, Well-007349, Project No: 0496.00

Page 6

#### Attachments:

Figure 1: Topographic Well Location Map

Figure 2: Humboldt County Assessor's Parcel Map

Figure 3: Satellite Image of Well location

Figure 4: Geologic Map

Figure 4a: Geologic Map Explanation Figure 5: Geologic Cross Section

Figure 6: Hydrogeologic Cross Section

Figure 7: USDA-NRCS Soils Map

# State of California Well Completion Report:

WCR2009-007349 (e0096711), APN: 211-184-006 (Subject Well)


# Web Soil Survey, NRCS Map Unit Description:

Wirefence-Windynip-Devilshole complex, #646, 5 to 30 percent slopes.

### Reference:

Flint, et al.: Fine-scale hydrologic modeling for regional landscape applications: the California Basin Characterization Model development and performance. Ecological Process, 2013, 2:25. (doi:10.1186/2192-1709-2-25)

Lindberg Geologic Consulting	Engineering-Geologic Well Connectivity Assessment Report	Figure 1
Post Office Box 306	Perimeter (Rim) Road, Panther Gap, Honeydew, APN: 211-184-006	December 22, 2022
Cutten, CA 95534	Well WCR2009-007349 (e0096711), Ms. Marion Collamer, Client	Project 0496.00
(707) 442-6000	Topographic Well Location Map (locations approximate)	1" ≈ 2,500'



Lindberg Geologic Consulting	Engineering-Geologic Well Connectivity Assessment Report	Figure 2
Post Office Box 306	Perimeter (Rim) Road, Panther Gap, Honeydew, APN: 211-184-006	December 22, 2022
Cutten, CA 95534	Well WCR2009-007349 (e0096711), Ms. Marion Collamer, Client	Project 0496.00
707) 442-6000	Humboldt County Assessor's Parcel Map (locations approximate)	1" ≈ 2,100
SECS 28, 29, 30, 31, 32 8, 33, 28 2E  SECS 28, 29, 30, 31, 32 8, 33, 28 2E  SECS 28, 29, 30, 31, 32 8, 33, 28 2E  SECS 28, 29, 30, 31, 32 8, 33, 28 28 33, 28 28 27  SECS 28, 29, 30, 31, 32 8, 33, 28 28 27  SECS 28, 29, 30, 31, 32 8, 33, 28 28 27  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28 27  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28 28  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28  SECS 28, 29, 30, 31, 32 8, 33, 38 28 28  SECS 28, 29, 30, 31, 32 8, 33, 38 28  SECS 28, 29, 30, 31, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32 8, 32	(B) 318.984 (B) 1.604 (B) 3.804 (B)	S.H.U. COMP. 1 (221) 56 4 (221) 4 3

Lindberg Geologic Consulting	Engineering-Geologic Well Connectivity Assessment Report	Figure 3	
Post Office Box 306	Perimeter (Rim) Road, Panther Gap, Honeydew, APN: 211-184-006	December 22, 2022	
Cutten, CA 95534	Well WCR2009-007349 (e0096711), Ms. Marion Collamer, Client	Project 0496.00	
(707) 442-6000	Satellite Image of Well Location (locations approximate)	1" ≈ 600'	



Lindberg Geologic Consulting	Engineering-Geologic Well Connectivity Assessment Report	Figure 4								
Post Office Box 306	Perimeter (Rim) Road, Panther Gap, Honeydew, APN: 211-184-006	December 22, 2022								
Cutten, CA 95534	tten, CA 95534 Well WCR2009-007349 (e0096711), Ms. Marion Collamer, Client									
(707) 442-6000										
	Geologic Map (locations approximate)  Well-Location  To a part of the control of	Project 0496.00 1" ≈ 5,000'								
	55 76	They b								
	Modified from: McLaughli	in, et al., (2000) N ≅ <b>1</b>								


Lindberg Geologic Consulting	Engineering-Geologic Well Connectivity Assessment Report	Figure 4a	
P. O. Box 306	Perimeter (Rim) Road, Panther Gap, Honeydew, APN: 211-184-006	December 22, 2022	
Cutten, CA 95534	Well WCR2009-007349 (e0096711), Ms. Marion Collamer, Client	Project 0496.00	
(707) 442-6000	Geologic Map Explanation	No Scale	

#### DESCRIPTION OF MAP UNITS GREAT VALLEY SEQUENCE OVERLAP ASSEMBLAGE **QUATERNARY AND TERTIARY OVERLAP DEPOSITS** Eastern Hayfork subterrane Qal Alluvial deposits (Holocene and late Pleistocene?) Chert (Late Cretaceous to Early Jurassic) eh Undeformed marine shoreline and actian deposits Basaltic rocks (Cretikeous and Jurassic) Qm (Holocene and late Pleistocene) Undwided blueschist blocks (Jurassic?) Limestone Undifferentiated nonmarine terrace deposits Holocene and Pleistocene) Greenstone Serpentinite Landshide deposits (Holocene and Pleistocene) Metachert Western Hayfork subterrane QTog Metasandstone of Yolla Bolly terrane, undivided Older alluvium (Pielstocene and Jor) Pliocene) Hayfork Bally Meta-andesite of Irwin (1985), undivided (Middle Jurassic) whu Marine and nonmarine overlap deposits (late Pleistocene to middle Miocene) Melange block lithology unknown Wildwood (Chanchelulia Peak of Wright and Fahan, 1988) pluton (Middle Jurassic) whwg -- Eastern Belt --Volcanic rocks of Fickle Hill (Oligocene) Pickett Peak terrane (Early Cretaceous or older) whwp Clinopyroxenite COAST RANGES PROVINCE Metasedimentary and metavolcanic rocks of the Pickett Peak Diorite and gabbro plutons (Middle? Jurassic) terrane (Early Cretaceous or older) Battlesnake Creek terrane -- Coastal Belt --South Fork Mountain Schill rem Melange (Jurassic and older) Chinquapin Metabasalt Member (Irwin and others, 1974) Coastal terrane/Pilocene to Late Cretaceous) Sedimentary, igneous, and metamorphic rocks of the Coastal terrane (Pliocene to Late Cretaceous). ppv Valentine Springs Formation Metabasalt and minor metachert Melange col Volcanic Rocks (Agrassic or Triassic) Yolla Bolly terrane (Early Cretaceous to Middle Jurassic?) co2 Melange Intrusive complex (Early Jurassic or Late Triassic) rcic Metasedimentary and metalgneous rocks of the Yolla Bolly terrane (Early Cretaceous to Middle Jurassic?). co3 Broken sandstone and argillite FCD Plutonic rocks (Early Jurassic or Late Triassic) Taliaferro Metamorphic Complex of Suppe and Armstrong (1972) (Early Cretaceous to Middle Jurassic?) ybt roum Ultramatic rocks (age uncertain) Basaltic Rocks (Late Cretaceous) repd Chicago Rock melange of Blake and Jayko (1983) (Early Cretaceous to Middle Jurassic) Limestone (Late Cretaceous) Western Klamath terrang Undivided blueschist (Jurassic?) Greenstone Smith River subterrane King Range terrane Miocene to Late Cretaceous) Metacheri STS Galice?formation (Late Jurassic) Kip Igneous and sedimentary rocks of Point Delgada (Late Cretaceous) Metagraywacke of Hammerhorn Ridge (Late Jurassic to Middle Jurassic) srv Pyroclastic andesite Undivided blueschist blocks (Aurassic?) Glen Creek gabbro-ultramatic complex of irwin and others (1974) srab srpd Serpentinized peridotite Melange and (on folded argillite sp kiki **MAP SYMBOLS** krk2 Highly folded broken formation Devils Hole Ridge broken formation of Blake and Jayko (1983) (Early Cretaceous to Middle Jurassic) - - - Contact Highly folded largely unbroken rocks - - - - - Tault kri Little Indian Valley argillite of McLaughlin and Ohlin (1984) (Early Cretaceous to Late Jurassic) Thrus fault ybi Trace of the San Andreas fault associated with 1906 earthquake rupture krb **Folia Bolly terrane** Rocks of the Yolla Bolly terrane, undivided Folse Cape terrane (Miocene? to Oligocene?) Strike and dip of bedding: edimentary rocks of the False Cape terrane 19 39 Inclined GREAT VALLEY SEQUENCE AND COAST RANGE OPHIQUITE (Miocene? to Oligocene?) Yager terrane (Eocene to Paleocene?) Elder Creek(\*) terrane **(D)** Horizontal Sedimentary rocks of the Yager terrane (Eocene to Paleocene?) ecms Mudstone (Early Cretaceous) Overturned y1 ecg y2 ecsp Serpentinite melange Highly folded little-broken sandstone, у3 Strike and dip of cleavage Del Poerto (2) tempre Shearfolation Yegl Conglomerate Rocks of the Del Puerto(7) terrane Inclined - Central belt -Modstone (Late Jurassic) Vertical Melange of the Central belt (early Tertiary to Late Cretaceous): Coast Range ophiolite (Middle and Late Jurassic) Folds: Unnamed Metasandstone and meta-argilline (Late Cretaceous to Late Jurassic) Tuffaceous chert (Late Jurassic) Synclinal or synformal axis Basaltic flows and keratophyric tuff (Jurassic?) Melange cm1 - Anticimal or antiformal axis dpd Diabase (Jurassic?) cm2 Melange Overturned syncline dpsp Serpentinite melange (Jurassic?) cb1 Broken formation Landshile 5p Undivided Serpentinized peridotite Chirassic? cb2 Melange Blocks ite Rock metasandstone of Jayko and others (1989) KLAMATH MOUNTAINS PROVINCE CWF (Paleogene and [or] Late Cretaceous) Undwided Great Valley Sequence. П chr Haman Ridge graywacke of Jayko and others (1989) (Cretaceous?) Sedimentary rocks (Lower Cretaceous) 0 Blueschist Fort Seward metasandstone (age unknown) Greenstone Limestone (Late to Early Cretaceous)

GEOLOGY OF THE CAPE MENDOCINO, EUREKA, GARBERVILLE, AND SOUTHWESTERN PART OF THE HAYFORK 30 X 60 MINUTE QUADRANGLES AND ADJACENT OFFSHORE AREA, NORTHERN CALIFORNIA (McLaughlin et al., 2000)


Lindberg Geologic Consulting	Engineering-Geologic Well Connectivity Assessment Report	Figure
Post Office Box 306	Perimeter (Rim) Road, Panther Gap, Honeydew, APN: 211-184-006	December 22, 202
Cutten, CA 95534	Well WCR2009-007349 (e0096711), Ms. Marion Collamer, Client	Project 0496.
(707) 442-6000	Geologic Cross Section (locations approximate)	Not to Sca
Well Location	ecsp ecsp Ols of the color of t	Modified from: McLaughlin, et al., 2,000
	<del>g</del>	
	dsoa 	
	( m	
	§ <del></del>	

Lindberg Geologic Consulting	Engineering-Geologic Well Connectivity Assessment Report	Figure 6
Post Office Box 306	Perimeter (Rim) Road, Panther Gap, Honeydew, APN: 211-184-006	December 22, 2022
Cutten, CA 95534	Well WCR2009-007349 (e0096711), Ms. Marion Collamer, Client	Project 0496.00
(707) 442-6000	Hydrogeologic Cross Section (locations approximate)	V. E. = 2



flow in this cross section is southwesterly, toward from the viewer, or out of the page. Groundwater is presumed to flow from recharge Groundwater is envisioned to flow through fractured bedrock. Fractures are interpreted to be the primary permeability, providing In this vertically exaggerated (~2x) cross section, the view is looking to the northeast toward the Bull Creek divide. Groundwater areas in the higher ground to the northeast. This well is sited high on the ridge above Westlund Creek valley. Subgrade is composed of interbedded argillite and sandstone of the Yager Terrane (y1), a component of the Coastal Belt of the Franciscan Complex. preferential flow paths for the local groundwater. The driller noted that first water occurred 110 feet below the surface. Static water occurred 100 feet below the surface. A sanitary surface seal was installed by the driller for the ground surface to the 20-foot depth. This well is cased to 100 feet below the existing ground surface, screened from 100 to 200 feet, where this well draws groundwater. Bedrock subgrade mapping (Figure 4), is from McLaughlin, et al., (2000)

Lindberg Geologic Consulting	Engineering-Geologic Well Connectivity Assessment Report	Figure 7
Post Office Box 306	Perimeter (Rim) Road, Panther Gap, Honeydew, APN: 211-184-006	December 22, 2022
Cutten, CA 95534	Well WCR2009-007349 (e0096711), Ms. Marion Collamer, Client	Project 0496.00
(707) 442-6000	USDA-NRCS Soil Map (locations approximate)	Scale Not Determined



'The free	Adobe F	Peader ma	y be used to vie	w and compli	ete this form	Source	or software in	sat be purchas	sed to compl	950 S2VE	and reaso	a sayed fo	orm.	
File Origi							State of Cal					DWR Use Only - Do Not Fill In		
Page 1 of 2 Well Complete							on Report					No ordered		
Owner's Well Number 1 No. a009.38														
Date Work Began 06/18/2009 Date Work Ended 6/26/2009							Longitude Longitude							
			mbolet Cour									APNY	RSOM	* - L - L -
Perma N	umber.	08/09-0			Date <u>5/8/06</u>									
				logic Log							Weil	Owner	_	
		s @Ver Air Drilling		orzontal	O Angle Delling Flu		dly		Greo Este					
		urface		De	acription	RI PU			Address 5	00 F St	Suita	3 9708	CA	95521
Feet	10	Feet		scribe maten	el graiq siza, o	color, et	k	City Arcets State CA Zip 95521						
0	68		Fractured W		Bedrock	_		Well Location						
68	200		Fractured Be	edrock	_	_			Address None Assigned Cay Honey Dew County Mumboldt					
<u> </u>	+-	-				_			oney Dew				many	, AJ
		-				-		Latitude	Dec	Min	Sec	N Longiku	- C	en Mas Sec
		1				_		Datum_		Decimal	Lat		_ Dea	mel Long
						_		APN 80	ch 211	Page	184		Paro	06
								Townsh	ip	Range	e		Secti	on
								1	Locat	ion Ske	tch			Activity
								(Situation)	must be drown	North	ber form is	printed,)		ew Well odification/Repair
								11-		Page 67			- (	Deepen
								11				- 1		Other
								]				- 1	- 0	estroy
								]						Planned Uses
								11				- 1	-	rater Supply
	-							41				- 1		Domestic Public
	-							Mean						Irrigation   Industrial
	-							115				-	00	athodic Protection
	+	- +				_		-{				- 1		ewatering
								-{				- 1		eat Exchange
	-	-						-11				1		jection lonitoring
	-	1						-11				Ĭ		amediation
	+-	$\rightarrow$						-11						parging
	1	-		-				11.		South			OT	ost Well
	1	_						Gustrain or a	moribe (etemps	of word from to	ade building	. Tencos		apor Extraction
	-	-						Process in a	of althorism reap nowally and spen	Clara Substitution of Clarks	J paper 1 nes	andary.	00	ther
	1							Water L	evel and	Yield c	of Com	pleted V	Vell	
									first water	110			_ (Fee	it below surface)
								Oepth to Water L	Static swel 100	i.	(Fee	d) Date	S. San com	med 06/18/2009
Total De	oth of B	ioring	200			Feet		Estimate	ed Yield *	20		M) Test		
Total De	oth of C	omeleter	1 Weit 200			Feet		Test Ler	ngth 4.0		{Hou	urs) Total	Drawt	fown 200 (Feet)
								'May no	t be repres	entative	of a wel	i's long to	erm yfe	id.
Denth I		Street, etc.		Cas	ings	18/-19	D 4-74					Annul	ar Ma	terial
Depth f Surfe	C#	Screhole Clameter		Mate	rial Th	Wall ickness	Outside s Diameter	Screen Type	Slot Size If Any		h from rface	PI		Description
Feet to	Feet 00	(linches)		In 10 2 2 2		nches)			(Inches)	Feet	to Feet			Description.
-	200	10	Blank Somen	PVC Seh, St PVC Seh, B	NAME OF TAXABLE PARKS	200	The second second	Mary A file	0.000	0	20	Benionite	-	Sanitary Seal
100 2		10	OCIDER	PVG aux B	9 0	LEUU	9	Milled State	0.032	20	200	Filter Pa	OK .	3/8" Pea Gravel
_														THE PERSON NOT (SEE
							1000 100	100	1000		200			
o Bull	10 L	<b>国籍</b>		LO EL CO			2011		DOM:				LESSON	
Attachments						Certification Statement								
Geologic Log I, the undersigned, certify that the						of this report	is complet	e and ac	Canale I	o the her	t of me	Separate and history		
										te and accurate to the best of my knowledge and belief				
Geophysical Log(s) SolfWater Chemical Analyses					3150,10	HNS	ON ROAD	Trible Co.	HYD	ESVILL	E	0	A 1	95547
		Chemic cation N			Signed	I	Some			City		5	<b>200</b>	Ze
NO ASSESS						087 LE	printed Wilder VI	let Contractor		-	08/27/ Deta Si		8388	
IF ADDITIONAL SPACE IS NEEDED, US							USE NEXT CO	ASEC.MVIII	Y BE NOTE OF	ED EDGE	Alsea C	-OF LE	zense Number	

# **Humboldt County, South Part, California**

# 646—Wirefence-Windynip-Devilshole complex, 5 to 30 percent slopes

#### Map Unit Setting

National map unit symbol: 1lpq7 Elevation: 200 to 3,280 feet

Mean annual precipitation: 60 to 100 inches
Mean annual air temperature: 48 to 57 degrees F

Frost-free period: 240 to 300 days

Farmland classification: Not prime farmland

#### **Map Unit Composition**

Wirefence and similar soils: 35 percent Windynip and similar soils: 30 percent Devilshole and similar soils: 20 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of

the mapunit.

#### **Description of Wirefence**

#### Setting

Landform: Ridges

Landform position (two-dimensional): Backslope, summit Landform position (three-dimensional): Mountaintop

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Colluvium and residuum derived from sandstone

#### Typical profile

A1 - 0 to 11 inches: loam A2 - 11 to 21 inches: loam

A3 - 21 to 33 inches: gravelly loam AB - 33 to 46 inches: gravelly loam

Bw - 46 to 63 inches: very gravelly fine sandy loam C - 63 to 79 inches: very gravelly fine sandy loam

#### Properties and qualities

Slope: 5 to 30 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0

mmhos/cm)

Available water supply, 0 to 60 inches: High (about 9.1 inches)

#### Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Ecological site: F004BI106CA - High precipitation mountain slopes

Hydric soil rating: No

### **Description of Windynip**

#### Setting

Landform: Ridges

Landform position (two-dimensional): Shoulder, summit Landform position (three-dimensional): Mountaintop

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Colluvium and residuum derived from sandstone

and mudstone

### Typical profile

A1 - 0 to 5 inches: loam
A2 - 5 to 12 inches: clay loam
A3 - 12 to 20 inches: clay loam
AB - 20 to 33 inches: clay loam

Bt1 - 33 to 59 inches: gravelly clay loam
Bt2 - 59 to 79 inches: very gravelly clay loam

#### Properties and qualities

Slope: 5 to 30 percent

Surface area covered with cobbles, stones or boulders: 0.0 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Capacity of the most limiting layer to transmit water

(Ksat): Moderately low to moderately high (0.06 to 0.60 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0

mmhos/cm)

Available water supply, 0 to 60 inches: Moderate (about 8.3 inches)

#### Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: C

Ecological site: R004BI202CA - Loamy Uplands


Hydric soil rating: No

#### **Description of Devilshole**

#### Setting

Landform: Ridges

Landform position (two-dimensional): Shoulder, summit



Landform position (three-dimensional): Mountaintop

Down-slope shape: Convex, linear Across-slope shape: Linear, convex

Parent material: Residuum weathered from sandstone and/or

mudstone

#### Typical profile

A - 0 to 4 inches: gravelly loam

ABt - 4 to 16 inches: very gravelly loam Bt - 16 to 28 inches: very gravelly loam

BCt - 28 to 47 inches: extremely gravelly loam

C - 47 to 61 inches: gravel

#### Properties and qualities

Slope: 5 to 30 percent

Surface area covered with cobbles, stones or boulders: 0.0 percent Depth to restrictive feature: 39 to 59 inches to strongly contrasting

textural stratification

Drainage class: Well drained

Capacity of the most limiting layer to transmit water

(Ksat): Moderately low to moderately high (0.14 to 1.42 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0

mmhos/cm)

Available water supply, 0 to 60 inches: Low (about 4.3 inches)

#### Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Ecological site: R004BI203CA - Loamy-skeletal Uplands

Hydric soil rating: No

#### **Minor Components**

#### Yorknorth, moist

Percent of map unit: 6 percent Landform: Mountain slopes

Landform position (two-dimensional): Footslope, backslope Landform position (three-dimensional): Mountainflank

Down-slope shape: Concave, linear

Across-slope shape: Concave, linear

Hydric soil rating: No

### Crazycoyote

Percent of map unit: 5 percent Landform: Mountain slopes

Landform position (two-dimensional): Backslope Landform position (three-dimensional): Center third of

mountainflank

Down-slope shape: Concave, convex, linear

Across-slope shape: Linear

Hydric soil rating: No

#### Rainbear

Percent of map unit: 4 percent
Landform: Ridges, mountain slopes
Landform position (two-dimensional): Shoulder
Landform position (three-dimensional): Mountainflank
Down-slope shape: Convex
Across-slope shape: Linear
Hydric soil rating: No

# **Data Source Information**

Soil Survey Area: Humboldt County, South Part, California

Survey Area Data: Version 12, Sep 2, 2022